

TRENCH'N edge™

Irrigation Trencher



Blows the trenched material directly onto tarps



Lay the pipe into the trench



Drop the dirt into the trench



No Mess, No Fuss, Just clean trenches - No Clean Up

For Smooth Curves and Less Work, Call 800-4-T-EDGER, (800-483-3437).
For the Edge, Inc., 8028 Hill Trail North, Lake Elmo, MN 55042-9534
Phone (651) 777-7923, Fax (651) 770-9430 www.trenchnedge.com
US Patent Number US05964049

The TRENCH'N edge Irrigation Trencher is the only portable irrigation trencher to have all of these unique features:

- Blows the trenched material onto tarps - to reduce clean-up labor.
- Steerable front pivot wheel.
- Cuts small-diameter turns-- as tight as 36" radius.
- No need to buy multiple blades for each depth and width.
- Can make multiple cuts for wider drain tile and main line watering systems
- Material can discharge on either side of machine for increased flexibility and reduced cleanup.
- 13 HP Honda engine to cut through tough clays and rocky soils.
- Cutting wheel centered between the rear wheels for a uniform trench during tight radiuses.
- Narrow machine design to allow closer cuts next to foundation walls.
- Trencher teeth are replaceable carbide tip frost points or shark teeth.
- Spring loaded retractable cutting blade to reduce maintenance costs.
- All blades and belts enclosed in steel housing for operator safety.
- Portable compact design for easy loading in minivans and pickups.
- Trench for waterlines, sprinkler systems, lighting cable, drain tile, landscape walls, and edging.

Specifications



Tight radiuses down to 36"

Continuous runs - No corner fittings

Engine:	13 HP Honda
Landscape trencher cut:	Up to 5" wide x 6" deep
Irrigation trencher cut:	Up to 2.5" or 1.75" wide x 0-12" deep
Speed:	Up to 20 feet per minute, varies with ground conditions
Discharge:	Dual side: displaced soil can be discharged into or out of a bed, on either side of machine
Drive:	Double V-belt with Idler Clutch from engine to rotor and optional 3" centrifical clutch available
Trencher Teeth:	Up to 8 replaceable Carbide Bits mounted in forged steel holdlers
Service Parts:	Standard components may be obtained locally
Dimensions:	70" long x 25" wide x 38" high with extension or 25" compacted
Weight:	275#
Shipping:	70" x 38" x 25", 25.3 cubic feet, 350#
Assembly:	Fully Assembled from Factory

For Smooth Curves and Less Work, Call 800-4-T-EDGER, (800-483-3437).
For the Edge, Inc., 8028 Hill Trail North, Lake Elmo, MN 55042-9534
Phone (651) 777-7923, Fax (651) 770-9430 www.trenchnedge.com
US Patent Number US05964049